

Hydrogeological studies and groundwater modelling in the project sites in Finland

EU LIFE Project EC Meeting

16th April 2025


Anna Autio, Omar Nimr, Khizer Jadoon, Pertti Ala-Aho, Hannu Marttila

Water, Energy and Environmental Engineering Research Unit

University of Oulu



Hydrological monitoring



-First indicator of successful restoration

Setup:

-Short open-pipe piezometers in ~80 locations to monitor shallow WT as part of GHG & vegetation plots

-Long deep piezometers in 14 locations to monitor hydraulic gradients

--~20 operating remote loggers (14 in long piezometers and ~6 short open-pipe piezometers)

-First sensors installed in November 2022





Key reached milestones for hydrological studies and modelling in 2024

Field work activities:

- Winter Ground Penetrating Radar (GPR) campaign on the 4th-8th April 2024
- Installation of remaining monitoring wells and sensors in May 2024
- Summer GPR campaign on the 9th-13th June 2024
 - Two seismic refraction lines
 - Manual peat depth probing
- Autumn manual GW monitoring and piezometer mapping campaign 23rd-27th September

Modelling and data analysis:

- Steady-state model of Matorovasuo construction and management scenario modelling (pristine/pre-management, drained, restored)
- Mesh update and testing for the Pallaslompo model
- Geophysical data processing and interpretation
- Geological model building
- Monitoring data preliminary processing and analysis





Geophysical and geological measurements

- Ground Penetrating Radar (GPR)
 - Winter 2024 campaign covered 14.2 km (100MHz shielded and 50 MHz RTA antennas)
 - Summer 2024 campaign covered 12.402 km (50 MHz RTA antenna)
- Seismic refraction
 - 2 lines with a total length ~220 m in Pallaslompolo catchment
- Manual peat depth probing in 73 locations


Geophysical measurements were done and analysed for the Master's thesis of Khizer Jadoon (to be submitted February/March 2025)






Geophysical data - interpretations

Seismic refraction



Scale = 1 / 1000

GPR



Seismic refraction

- Seismic refraction measurements confirmed the bedrock interface derived from GPR data



Synthesis – Peat depths

Synthesis
of the geophysical geological
data done by Khizer Jadoon
in his Master's thesis:
*Geophysical Investigations
of Pallas-Yllästunturi Region
Using GPR and Seismic
Refraction, April 2025*





Figure by Khizer Jadoon




Synthesis – Bedrock depth





Synthesis – Glaciofluvial deposits






Välisuo







Välisuo mire monitoring

- Currently 7 operating remote WT loggers (Decentlab-26)
- First measurements starting in November 2022
- Additional piezometers in mineral soil within the whole catchment area allow for holistic tracking of the hydrological state holistically






Hydrological monitoring first results

- Preliminary analysis indicates that WT levels in well drained peatland areas experienced less drop during summer time in comparison to wetter undrained (less affected areas) in both peatlands.
- peatlands' hydrological state and its dynamics are dependent on the preceding hydrological state so these first indications need to be confirmed by continuing monitoring and numerical modelling



GW levels fluctuations by year in PZ7


Increasing water levels in late autumn and early winter



Välisuo


Deep peatland piezometer

GW levels fluctuations by year in PZ24



Deep GW



GW levels fluctuations by year in PZ8



GW levels fluctuations by year in PZ6



GW levels fluctuations by year in PZ7



→ Direction of hydraulic gradient

Välisuo model

- Objectives
 - Forecasting hydrological observations -> validation of hydrological conditions for carbon balance simulation
- Integrated physically based groundwater-surface water (GW-SW) modelling with HydroGeoSphere
- Modified model for whole Pallaslompol catchment
 - Hypothesis: In successfully restored fen/aapa mire system GW input to mire should significantly increase
 - Densified mesh to include implicitly various restoration structures

Journal of Hydrology 626 (2023) 130342



ELSEVIER

Contents lists available at ScienceDirect

Journal of Hydrology


journal homepage: www.elsevier.com/locate/jhydrol



Research papers

Groundwater exfiltration pattern determination in the sub-arctic catchment using thermal imaging, stable water isotopes and fully-integrated groundwater-surface water modelling

Anna Autio ^{a,*}, Pertti Ala-Aho ^a, Pekka M. Rossi ^a, Anna-Kaisa Ronkanen ^{a,b}, Mika Aurela ^c, Annalea Lohila ^{c,d}, Pasi Korpelainen ^e, Timo Kumpula ^e, Björn Klöve ^a, Hannu Marttila ^a




Matorovasuo








Matorovasuo monitoring

- Currently 12 (+3) operating remote WT loggers (Decentlab-26)
- First measurements starting in November 2022




Matorovasuo




→ Direction of hydraulic gradient

Matorovasuo modelling (Proof of concept)




Terrain models/ computational meshes


Pristine



Drained





Restored



13,000 surface nodes
24,000 surface elements




Both drained and restored meshes
57,000 surface nodes
110,000 surface elements

Cont. terrain models/ computational meshes






13,000 surface nodes
24,000 surface elements


Cont. terrain models/ computational meshes





Cont. terrain models/ computational meshes




Subsurface domains representation in HGS




Section A-A




Section B-B



Restoration activities – implementation in the model




Adjusting the restoration activities to the model




Steady state simulation results

Pristine Setup




Cont. steady state simulation results

Drained Setup




Cont. steady state simulation results

Restored Setup





- Are they recharging (infiltration) pools/ or discharging (exfiltration) pools (?)

- Emerging of new water pools
- Global rising in GWT, specially in eastern, central and northern bogs




How restoration activities perform (?)

Effect of peat-dams (water retaining/ flooding)






How restoration activities perform (?)

Effect of ditch-filling (groundwater diffuses at the tips of unfilled ditches)



Hydrograph source separation using HGS+HMC (old/ new waters)




Hydrograph source separation using HGS+HMC (old/ new waters)


Drained Catchment Management

%old 46.38
%new 53.62


Collective outflow
from all the outlets






Old water - drained management



New water - drained management



Hydrograph source separation using HGS+HMC (old/ new waters)









GW wells

PZ18: Western peatlands are almost unaffected in terms of GWT drop

PZ10: Central undisturbed (non-ditched) peatlands still affected considerably with a drop of 1.5m approx.

PZ15: Northern most/ east peatlands are significantly affected by the drainage; almost 5.0m drop in gwl





Thank you